












TECHNICAL CHARACTERISTICS

PURLINE organic flooring wineo 1000 to click Permanently elastic polyurethane flooring according to EN 16776 free of chlorine, solvents and plasticizers				wineo	
 to click	wood L	wood XL	stone L		
Format	1295 x 195 mm	1507 x 246 mm	642 x 330.5 mm		
Product thickness	5 mm	5 mm	5 mm		
Profile connection	Fold-Down 	Fold-Down 	LocTec 		
Weight	9 kg/m ²	9 kg/m ²	9 kg/m ²		
Planks / m² per box	8 / 2.02 m ²	6 / 2.22 m ²	10 / 2.12 m ²		
Boxes / m² per pallet	56 / 113.12 m ²	48 / 106.56 m ²	52 / 110.24 m ²		
Guarantee	Life Time Guarantee for private use according to Windmüller warranty conditions – www.wineo.de				
Classification			Product composition		
 Utilization class 23 EN ISO 10874	Domestic area with intensive usage		1		Top element <ul style="list-style-type: none"> • PU-top layer with surface structure • decor paper • stabilisation
 Utilization class 32 EN ISO 10874	Commercial sector with average usage				
 R9 Anti slip category DIN 51130	R 9		2	Profile connection Fold-Down locking (wood) LocTec locking (stone)	
 Staining and chemical resistance EN ISO 26987	Very good resistance according to the concentration and residence time				
 Light fastness EN ISO 105-B02	~ 7		3	Base layer ecuran high performance composite material	
 Residual indentation EN ISO 24343-1	~ 0.05 mm				
 Effect of a furniture leg EN 424	Foot type 0 – no visible change		4	Backing Integrated Fleece TEC-System	
 Castor chair test EN 425	25000 revolutions no damage with rolls type W				
 Thermal resistance ISO 8302	0.01 (m ² K)/W		   <p>www.blauer-engel.de/uz120</p>     		
 Impact sound reduction EN ISO 10140	~ 6 dB ~ 16 dB in the system with silentCOMFORT				
 Dimension stability EN ISO 23999	~ 0.10 %				
REACH	free from SVHC substances ≥ 0.1 %				
Disposal	Private: possible with normal domestic refuse Commercial: Refuse-key-no. AVV 170203				
 Windmüller GmbH Nord-West-Ring 21 D-32832 Augustdorf DOP: 2001010 EN 14041:2004 / AC2006 1658      www.wineo.de					
 ÉMISSIONS DANS L'AIR INTÉRIEUR A+ A+ A B C Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)					
  					

Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.